

TB-4045-DIN

DIN Mountable Fanless PC



Key Highlights

- Intel Quad-Core Celeron J1900 CPU
- Wide Operating Temp (-20°C – 70°C)
- DIN Rail Mountable
- Fanless, Rugged Housing

[VIEW ONLINE](#)

The TB-4045-DIN is built for tough environments where dust, heat and machine vibration would damage a consumer-grade computer. It can be mounted onto a DIN rail on your production line, in a control cabinet or on your shop floor. The TB-4045-DIN is fanless and has a wide operating temperature range. Overall, it is much more rugged and reliable than a consumer-grade PC, but comes in at a similar price-point, allowing you to save overall cost, by cutting down on costly downtime and repairs or replacements.

USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

Technical Specifications

Primary Components

Processor Family	Intel Celeron Bay Trail
Processor Model	J1900 Quad Core
Processor Speed	2.0 GHz
Memory Type	1x DDR3L SO-DIMM
Memory Support	4GB, 8GB
Storage Type	1x 2.5" SATA Drive Bay for SSD/HDD, mSATA
Storage Support	32GB-2TB

Power

Input Voltage Range	9-36V DC, 24V required if POE out is utilized
---------------------	---

Thermal & Environmental

Operating Temperature	-20°C - 70°C (-4°F - 158°F)
Storage Temperature	-40°C - 85°C (-40°F - 185°F)
Cooling Solution	Passive - Fanless with Heatsink
Humidity Range	10% - 90% Non-condensing
Storage Humidity	10% - 90% Non-condensing

Weight / Dimensions

Weight	1.85 kg (4.1 lbs)
Dimensions	180 x 130 x 39.5 mm (7.1 x 5.1 x 1.6 in)

External I/O Ports

USB	1x USB 2.0, 1x USB 3.0
Serial / Com	2x COM
Serial Protocol Detail	1x RS-232/422/485 DB-9 (COM1), 1x RS-232 DB-9 (COM2)
Ethernet / LAN	3x RJ45 GbE LAN
Video Outputs	1x HDMI, 1x VGA
Other Ports	2 LAN ports support POE out (802.3af-combined 50W budget), 1x 8-bit GPIO (4x DI, 4x DO)
Audio Ports	1x Audio Line-Out
Power Input Port	2-Pin Power Switch, 3-Pin DC-In (Phoenix Type)

Operating Systems

Windows	Windows 10 IoT, Windows 10 Pro, Windows 7 Pro
Linux	Linux (Contact your sales rep for more information)

Enclosure

Material	Titanium Aluminum
Color	Black, Gray
Mounting Options	DIN Rail Mount

Certification

Certifications	ANSI C63.4, CE, FCC Class A, IEC 61000-3-2 (EMC), IEC 61000-3-3 (EMC), IEC 61000-4 (ESD)
----------------	--

Warranty

Warranty	Up to 5 Years
----------	---------------

Specifications subject to change.

USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com


EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

I/O Diagram Images



USA


Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA





Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw



180 mm

39.5 mm

130 mm



USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw