

TB-2945-DIN

Fanless Box PC with DIN Rail Mount



Key Highlights

- Intel Celeron N2930 Quad Core (2M Cache, Up to 2.16GHz)
- Designed for DIN Rail Mount
- Wide Range DC Power Input (9~36VDC)
- Steel Chassis with Aluminum Heatsink
- Ultra Slim, Fanless Design
- Optional GPIO

[VIEW ONLINE](#)

The TB-2945-DIN fanless box computer is partner to the TB-2945. The major difference is the TB-2945-DIN can be mounted on a DIN rail to save space and integrate seamlessly into your industrial environment. The DIN rail mounting system makes installation a breeze and allows industrial control equipment to be mounted conveniently next to each other. The TB-2945-DIN has an easy-access 2.5" SATA2 HDD Bay, 6 USB ports, and 2 Mini-PCIe expansion slots. This box computer has a wide range 9V to 36V DC power input, and the fanless cooling system allows it to operate in a wide temperature range from 0 to 50 °C (-20 to 60°C optional). The ultra slim design and wall mount make this box PC ideal for industrial control, manufacturing, and machine automation applications.

USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

Technical Specifications

Primary Components

Processor Family	Intel Celeron Bay Trail
Processor Model	N2930
Processor Speed	1.83 GHz
Memory Type	1x DDR3L SO-DIMM
Memory Support	4GB, 8GB
Storage Type	1x 2.5" SATA Drive Bay for SSD/HDD
Storage Support	32GB-1TB

Power

Input Voltage Range	9-32V DC
Max Power Consumption	17W

Thermal & Environmental

Operating Temperature	0°C - 50°C (32°F - 122°F), -20°C - 60°C (Optional -4°F - 140°F)
Storage Temperature	-30°C - 70°C (-22°F - 158°F)
Cooling Solution	Passive - Fanless with Heatsink
Storage Humidity	10% - 90% Non-condensing

Weight / Dimensions

Weight	1.3 kg (2.9 lbs)
Dimensions	180 x 130 x 55 mm (7.1 x 5.1 x 2.2 in)

Warranty

Warranty	1 Year
----------	--------

Specifications subject to change.

External I/O Ports

USB	2x USB 3.0, 4x USB 2.0
Serial / Com	3x COM
Serial Protocol Detail	1x RS-232/422/485 DB-9, default RS-232(COM1), 1x RS-232 DB-9(COM2/3)
Ethernet / LAN	2x RJ45 GbE LAN
Video Outputs	1x HDMI, 1x VGA
Other Ports	Optional GPIO (4 x Input, 4 x Output) Replaces COM3
Audio Ports	1x Audio Line-Out
Power Input Port	3-Pin DC-In (Phoenix Type)

Operating Systems

Windows	Windows 10 IoT, Windows 10 Pro, Windows 7 Pro, Windows 8.1 Pro
---------	----------------------------------------------------------------

Enclosure

Material	Aluminum
Color	Gray
Led Indicator Light	HDD Access, Power
Control Buttons	Power Button
Mounting Options	DIN Rail Mount, Wall Mount

Certification

Certifications	CE, FCC Class A
----------------	-----------------

USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

I/O Diagram Images



USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

