

TB-4845-DIN

Industrial Mini PC DIN

Key Highlights



- Intel Celeron J6413 Processor
- Windows 11 Capabilities
- Fanless Cooling System
- DIN Rail mounting options
- Multiple Inputs and Outputs including 5x USB, 3x LAN and 2x COM

[VIEW ONLINE](#)

The TB-4845-DIN is a compact and powerful computing solution tailored for industrial applications. Equipped with an Intel Celeron J6413 CPU and running on Windows 11, it provides reliable performance and access to the latest software capabilities. With its DIN rail hardware design, it seamlessly integrates into space-constrained environments, making it ideal for general manufacturing setups. The TB-4845-DIN features multiple I/Os, enabling seamless connectivity with a variety of peripheral devices. This solution offers the perfect combination of compactness, power, and connectivity, making it an excellent choice for industrial computing needs in limited spaces.

USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

Technical Specifications

Primary Components	
Processor Family	Intel Celeron Elkhart Lake
Processor Model	Celeron J6413
Processor Speed	1.8 GHz, Up to 3.0 GHz
Memory Type	1x DDR4 SO-DIMM
Memory Support	32GB
Storage Type	1x M.2 SATA3 2242 Slot
Storage Support	M.2: 256GB-1TB

Operating Systems	
Windows	Windows 10 IoT, Windows 10 Pro, Windows 11 Pro

Compatibility	
Security Hardware	fTPM 2.0

Thermal & Environmental	
Operating Temperature	-20°C - 70°C (-4°F - 158°F)
Storage Temperature	-40°C - 85°C (-40°F - 185°F)
Cooling Solution	Passive - Fanless
Storage Humidity	10% - 90% Non-condensing

Weight / Dimensions	
Weight	1.9 kg (4.2 lbs)
Dimensions	180 x 130 x 55 mm (7.1 x 5.1 x 2.2 in)

Warranty	
Warranty	1 Year

Specifications subject to change.

External I/O Ports	
USB	1x USB 2.0 (Internal Type A on Motherboard), 2x USB 2.0, 2x USB 3.1
Serial / Com	2x COM
Ethernet / LAN	3x RJ45 GbE LAN
Video Outputs	1x HDMI, 1x VGA
Other Ports	1x GPIO 8 bit
Power Input Port	DC-in Jack (Phoenix Type)

Power	
Input Voltage Range	9-36V DC
Max Power Consumption	40W
Standard Power Adapter	12Vdc, 5A, US AC power cord, 60W

Expansion Slots	
Internal M.2	1x M.2 3042/3052 Key B (For 4G/5G Cellular expansion option)

Enclosure	
Material	Aluminum
Color	Black
Led Indicator Light	HDD Access, Power
Mounting Options	DIN Rail Mount


Certification	
Certifications	CE, EN 55032/55035 and CISPR 32/35, EN50155 EMC, FCC, IEC 61000-3-2 (EMC), IEC 61000-3-3 (EMC), IEC 61000-4 (ESD), RoHS, UKCA

USA
Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE
Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA
Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

I/O Diagram Images



USA


Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

**USA**

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw