

TWB-5920

Waterproof Box PC



Key Highlights

- 11th Generation Core i5 Processor
- Windows 11 Capabilities
- Fanless Design
- Wide Operating Temperature (0C-50C)
- 9~36V DC with Isolation

[VIEW ONLINE](#)

The TWB-5920 stands as a pinnacle of durability and performance, boasting an IP65 Full Waterproof rating with a NEMA 4x enclosure, ensuring resilience against water and dust in demanding environments. Its ultra-compact design, complemented by an aluminum chassis, maximizes space efficiency without compromising durability. Powered by an 11th Gen Core i5 processor and equipped with Windows 11, this system delivers robust computing power and seamless functionality. Whether in rugged industrial settings or outdoor installations, the TWB-5920 offers unparalleled reliability, making it an ideal choice for applications where durability, performance, and efficiency are essential.

USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

Technical Specifications

Primary Components	
Processor Family	Intel Core I series 11th Generation Tiger Lake
Processor Model	Core i5-1135-G7
Processor Speed	2.4 GHz, Up to 4.2 GHz
Memory Type	1x DDR4 SO-DIMM
Memory Support	2GB, 4GB, 8GB, 32GB
Storage Type	1x M.2 M Key, PCIe or SATA, 2242 default or 2280
Storage Support	32GB-512GB

Operating Systems	
Windows	Windows 10 IoT, Windows 10 Pro, Windows 11 Pro
Linux	Linux Ubuntu 22.04 or above (Contact your sales rep for more information)

Expansion Slots	
Internal M.2	1x M.2 2230 Key E (for WiFi expansion option), 1x M.2 for NVME SSD Support

Enclosure	
Material	Aluminum
IP Rating	IP65
Color	Silver
Led Indicator Light	HDD Access, LAN, Power
Control Buttons	Power Button
Shock Rating	15g for 11ms
Mounting Options	Wall Mount

Warranty	
Warranty	Up to 5 Years

Specifications subject to change.

External I/O Ports	
USB	1x MI2 USB, 1x USB 2.0 Waterproof Connector with Cover
Serial / Com	1x MI2 8-pin for COM
Serial Protocol Detail	1x RS-232/RS-485/RS-422
Ethernet / LAN	2x MI2 8pin RJ45 Gbe LAN
Video Outputs	1x M21 Connector for HDMI
Power Input Port	MI2 type 3-PIN DC-in

Power	
Input Voltage Range	9-36V DC

Compatibility	
Security Hardware	TPM 2.0

Thermal & Environmental	
Operating Temperature	0°C - 50°C (32°F - 122°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Cooling Solution	Passive - Fanless
Humidity Range	10% - 90% Non-condensing

Weight / Dimensions	
Weight	3.2 kg (7.1 lbs)
Dimensions	261 x 193 x 51 mm (10.3 x 7.6 x 2.0 in)


Certification	
Certifications	Complies with FCC and CE Requirements

USA
Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE
Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA
Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw

Tech Diagram Images



USA

Teguar
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 866-693-3105
sales@teguar.com

EUROPE

Teguar Europe AG
Churerstrasse 54, CH-8808
Pfäffikon, Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA

Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1, Xintai 5th Rd.,
Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
+886 2 7751 5319
sales@teguar.com.tw