



Features

- 08" Full Flat Panel Touch Screen
- Bay Trail Celeron N2930 Quad-Core CPU
- Very low Power Use with Fanless Design
- Onboard DDR3L 4GB Memory
- IP66 Protected Front with Aluminum Housing
- 2 Pin Connector for Power Switch

Technical Specifications

Primary Components

| | |
|------------------|-------------------------------------|
| Processor Family | Intel Celeron Bay Trail |
| Processor Model | N2930 |
| Processor Speed | 1.83 GHz |
| Memory Type | Onboard DDR3 |
| Memory Support | 4GB |
| Storage Type | 1.8" Half Size MO297 SATA Drive Bay |
| Storage Support | 32GB-256GB |

Display

| | |
|--------------|---|
| Screen Size | 8" |
| Screen Ratio | 4:3 |
| Brightness | 350 nits, Optional 1000 nit High Brightness |

Touch Screen

| | |
|--------------|---------------------------------|
| Touch Screen | Projected Capacitive, Resistive |
|--------------|---------------------------------|

External I/O Ports

| | |
|------------------------|--|
| USB | 2x USB 3.0 |
| Serial / Com | 2x COM |
| Serial Protocol Detail | 1x RS-232/422/485 DB-9, default RS-232(COM1), 1x RS-232 DB-9(COM2) |
| Ethernet / LAN | 2x RJ45 GbE LAN |
| Video Outputs | 1x HDMI |
| Other Ports | 1x 2-Pin DC Power Switch Connector |
| Audio Ports | 1x Audio Line-Out |
| Power Input Port | 3-Pin DC-In (Phoenix Type) |

Power

| | |
|------------------------|----------------------------|
| Input Voltage Range | 9-36V DC |
| Standard Power Adapter | Optional 12V AC/DC Adapter |

Operating Systems

| | |
|---------|---|
| Windows | Windows 10 IoT, Windows 10 Pro, Windows 8.1 Pro |
| Linux | Linux (Contact your sales rep for more information) |

Thermal & Environmental

| | |
|-----------------------|---------------------------------|
| Operating Temperature | 0°C - 50°C (32°F – 122°F) |
| Storage Temperature | -20°C - 60°C (-4°F – 140°F) |
| Cooling Solution | Passive – Fanless with Heatsink |
| Humidity Range | 10% – 90% Non-condensing |

Enclosure

| | |
|------------------|----------------------------|
| Material | Aluminum |
| IP Rating | IP66 Front Bezel |
| Mounting Options | Panel Mount, VESA 75 Mount |

Peripherals & Wireless Connectivity

| | |
|-----------------------|------------------------|
| WiFi | Optional WiFi |
| Bluetooth | Optional Bluetooth 4.0 |
| Mobile Network 4G LTE | Optional 4G |

Weight / Dimensions

| | |
|------------|--|
| Weight | 1.8 kg (4.0 lbs) |
| Dimensions | 231 x 176 x 50 mm (9.1 x 6.9 x 2.0 in) |


Certification

| | |
|----------------|---------------------------|
| Certifications | CE, FCC Class A, UL 60950 |
|----------------|---------------------------|


Warranty

| | |
|----------|---------------|
| Warranty | Up to 5 Years |
|----------|---------------|

I/O Diagram Images



Tech Diagram Images



All specifications are subject to change without notice.