



Features

- 16" Resistive or P-Capacitive Touchscreen Display
- Multiple Inputs and Outputs including 4x USB, 1 Gb LAN, 2.5 Gb LAN, 3x COM and more
- Fanless Cooling System
- Windows 11 Capabilities
- Intel Celeron J6412 Processor

Technical Specifications

Primary Components

| | |
|------------------|--|
| Processor Family | Intel Celeron Elkhart Lake |
| Processor Model | Celeron J6412 |
| Processor Speed | 2.0 GHz |
| Memory Type | 2x DDR4 SO-DIMM |
| Memory Support | 32GB |
| Storage Type | 1x 2.5" SATA Drive Bay for SSD/HDD (Internal, not with removable drive in use), 1x M.2 SATA3 2280 Slot |
| Storage Support | M.2 and 2.5": 128GB - 1TB |

Display

| | |
|--------------|----------|
| Screen Size | 15.6" |
| Screen Ratio | 16:9 |
| Brightness | 400 nits |

Touch Screen

| | |
|--------------|---|
| Touch Screen | Projected Capacitive (Multi-touch), Resistive |
| Hardness | Resistive: 3H, P-cap: 7H |

External I/O Ports

| | |
|------------------------|--------------------------------------|
| USB | 2x USB 2.0, 2x USB 3.2 |
| Serial / Com | 3x COM |
| Serial Protocol Detail | 1x RS-232, 2x RS-232/422/485 |
| Ethernet / LAN | 1x RJ45 2.5 GbE LAN, 1x RJ45 GbE LAN |
| Video Outputs | 1x HDMI, 1x VGA |
| Audio Ports | 2x 3.5mm Audio Line-Out/Mic-In |
| Power Input Port | 4-Pole DIN (latching) |

Power

| | |
|------------------------|---------------------------------------|
| Input Voltage Range | 12-28V DC |
| Max Power Consumption | 63.5W |
| Standard Power Adapter | 60 watts, 100 ~240V AC in, 19V DC out |

Operating Systems

| | |
|---------|--|
| Windows | Windows 10 IoT, Windows 10 Pro, Windows 11, Windows 11 Pro |
|---------|--|

Compatibility

| | |
|-------------------|------------------|
| Security Hardware | Optional TPM 2.0 |
|-------------------|------------------|

Expansion Slots

| | |
|--------------|--------------------------------------|
| Internal M.2 | 1x M.2 Type B |
| Other | 1x SIM socket connected to M.2 B-Key |

Thermal & Environmental

| | |
|-----------------------|---------------------------------|
| Operating Temperature | 0°C - 45°C (32°F – 113°F) |
| Storage Temperature | -20°C - 65°C (-4°F – 149°F) |
| Cooling Solution | Passive – Fanless with Heatsink |
| Humidity Range | 10% – 90% Non-condensing |
| Storage Humidity | 10% – 90% Non-condensing |

Enclosure

| | |
|------------------|---|
| Material | Aluminum front bezel and SECC Steel Chassis |
| IP Rating | IP66 Front Bezel |
| Color | Black |
| Control Buttons | Power Reset |
| Mounting Options | VESA 75 Mount |

Weight / Dimensions

| | |
|------------|--|
| Weight | 6.5 kg (14.3 lbs) |
| Dimensions | 452 x 330 x 72 mm (17.8 x 13.0 x 2.8 in) |


Certification

| | |
|----------------|---------|
| Certifications | CE, FCC |
|----------------|---------|


Warranty

| | |
|----------|--------|
| Warranty | 1 Year |
|----------|--------|

I/O Diagram Images



Tech Diagram Images



All specifications are subject to change without notice.