



## Features

- 19" Resistive or PCAP Touchscreen
- Die Cast Aluminum Housing and IP66 Rated Front Bezel
- Designed for flexible IO expansion
- Windows 11 Capabilities

## Technical Specifications

### Primäre Komponenten

Processor Family	Intel Celeron Elkhart Lake
Processor Model	Celeron J6412
Processor Speed	2.0 GHz, Up to 2.6 GHz
Memory Type	1x DDR4 SO-DIMM
Memory Support	4GB, 8GB, 16GB, 32GB
Storage Type	1x M.2 SATA3 2242 Slot
Storage Support	M.2: 256GB-1TB

### Display

Screen Size	19
Screen Ratio	5:4
Brightness	350 nits, Optional 1000 nit High Brightness

### Touchscreen

Touch Screen	Projected Capacitive, Resistive
--------------	---------------------------------

### Externe E/A-Ports

USB	2x USB 2.0, 2x USB 3.2
Serial / Com	1x COM
Serial Protocol Detail	RS-232/422/485 (Default RS-232; select via BIOS)
Ethernet / LAN	2x RJ45 2.5 GbE LAN
Video Outputs	1x DisplayPort, supports DP++
Audio Ports	1x Audio Line-Out
Power Input Port	3-Pin DC-In (Phoenix Type)

### Leistung

Input Voltage Range	9-36V DC
Standard Power Adapter	Optional 12V AC/DC Adapter, 5A, 60W

## Batterie

Battery Type Optional Internal Battery

## Betriebssysteme

Windows Windows 10 IoT, Windows 10 Pro, Windows 11 Pro

## Erweiterungssteckplätze

Internal M.2 1x M.2 2230 Key E (for WiFi expansion option)

## Multimedia

Speakers Optional Speaker

## Thermisch & Umwelt

Operating Temperature 0°C - 50°C (32°F – 122°F), -20°C - 60°C (Optional -4°F – 140°F)

Storage Temperature -30°C - 70°C (-22°F – 158°F)

Cooling Solution Passive – Fanless with Heatsink

Humidity Range 10% – 95% Non-condensing

## Gehäuse

Material Aluminum

IP Rating IP66 Front Bezel

Color Gray

Mounting Options Panel Mount, VESA 100 Mount

## Peripheriegeräte und drahtlose Konnektivität

WiFi Optional WiFi

Bluetooth Optional Bluetooth 4.0

## Gewicht / Abmessungen

Weight 7.2 kg (15.9 lbs)

Dimensions 468 x 380 x 64.8 mm (18.4 x 15.0 x 2.6 in)

## Zertifizierung

Certifications CE, FCC, UL 62368

## Garantie

Warranty


Up to 5 Years

## I/O Diagram Images



- |                              |                       |
|------------------------------|-----------------------|
| <b>A</b> DC In               | <b>E</b> LAN (x2)     |
| <b>B</b> Audio Line Out      | <b>F</b> USB 3.2 (x2) |
| <b>C</b> Remote Power Switch | <b>G</b> COM          |
| <b>D</b> Display Port        | <b>H</b> USB 2.0 (x2) |

## Tech Diagram Images



*All specifications are subject to change without notice.*