



Features

- 21.5" Flat TFT LCD Touchscreen
- IP66/IP69K Fully Enclosed Fanless Design
- HDMI and VGA Inputs
- Grade 304 Stainless Steel Enclosure
- M12 Metal I/O Connectors

Technical Specifications

Display

Screen Size	21.5
Screen Ratio	16:09
Brightness	250 nits, Optional 1000 nit High Brightness

Touchscreen

Touch Screen	Projected Capacitive, Resistive
--------------	---------------------------------

Externe E/A-Ports

USB	1x M12 USB
Power Input Port	M12 type 3-PIN DC-in

Leistung

Input Voltage Range	9-36V DC
Max Power Consumption	18.9W

Thermisch & Umwelt

Operating Temperature	0°C - 50°C - 0°C - 40°C (32°F – 122°F (Standard), 32°F – 104°F (With High Bright LCD))
Storage Temperature	-30°C - 70°C (-22°F – 158°F)
Cooling Solution	Passive – Fanless
Humidity Range	10% – 90% Non-condensing

Gehäuse

Material	Optional SUS316 Stainless Steel, SUS304 Stainless Steel
IP Rating	IP66, IP69K
Control Buttons	On-Screen Display (OSD), Touchscreen Lock for Cleaning
Mounting Options	VESA 100 Mount, Yoke Mount

Gewicht / Abmessungen

Weight	9 kg (19.8 lbs)
Dimensions	571 x 362 x 55 mm (22.5 x 14.3 x 2.2 in)


Zertifizierung

Certifications	CE, FCC Class A
----------------	-----------------


Garantie

Warranty	Up to 5 Years
----------	---------------

I/O Diagram Images



Tech Diagram Images



All specifications are subject to change without notice.