

TP-7200-16

Pinnacle 15.6" Panel PC




Key Highlights

- Latest Fanless 14th Gen Meteor Lake CPU
- 15.6" High Brightness Display
- Direct Bonded Touch
- USB-C, Digital IO, HDMI Ports, Dual M.2 NVMe
- Stunning Sleek Form Factor
- Solid Cast-Aluminum Housing
- Windows 11 Pro and IOT

SHOP PINNACLE

The TP-7200-16 is designed to exceed your expectations wherever it's needed. Its Core Ultra processor offers extremely high performance while maintaining durability with a fanless cooling design. If you need a step further in the speed and efficiency department, add a boost in the form of a compatible Hailo card. Pinnacle requires less installation space than traditional models and features a direct bonded display with precisely responsive touch and great visual clarity, with either PCAP or resistive touch options.

Inputs/Outputs and 2D Drawing



Technical Specifications

Primary Components		Power	
Processor Model	Intel Core Ultra 5 125U	Input Voltage Range	12~24V DC
Processor Speed	Up to 4.3GHz	Max Power Consumption	60W
Memory Type	1x DDR5 SO-DIMM	Standard Power Adapter	Optional 90W 3-Pin Terminal Block PSU (19V/4.74A), Optional 100W USB-C PD PSU
Memory Support	32GB	Dimensions / Weight	
Storage type	M.2 2280 NVME SSD, M.2 2242 NVME SSD	Weight	3.1kg
Storage Support	128GB~1TB	Dimensions	379x231x48mm
Display		Cutout Dimensions	366x218mm
Screen Size	15.6"	Operating Systems	
Resolution	1920 x 1080 (Full HD)	Windows	Windows 11 IoT, Windows 11 Pro, Windows 10 IoT
Screen Ratio	16:9	Linux	Linux Ubuntu 24.04 or above
Brightness	800 nits	Enclosure	
Expansion		Ip Rating	IP65 Front Bezel
Other IO Ports	IO space reserved for customization. Can be 2nd COM, additional 2 USB 2.0 ports, or 8 pin GPIO/DIO	Mounting	Panel Mount, VESA 100 Mount
Other Specifications		Enclosure	Aluminum
Warranty	Up to 5 Years	Control Buttons	Power Button
Security Hardware	fTPM 2.0	Peripherals & Wireless Connectivity	
Certifications	CE, FCC	WiFi	Optional Wi-Fi 6E
Thermal and Environmental		BlueTooth	Optional Bluetooth 5.2
Operating Temperature	0°C – 50°C (32°F – 122°F)		
Storage Temperature	-20°C – 60°C (-4°F – 140°F)		
Cooling Solution	Passive Fanless with Heatsink		
Touch Screen			
Touch Screen	Projected Capacitive (Multitouch), Resistive		
External I/O ports			
USB	2x USB 3.2, 1x USB 3.2 Type-C (PD Input/DP Alt)		
Video Outputs	1x DisplayPort via USB-C, 1x HDMI		
Serial	1x COM		
LAN	1x GbE and 1x 2.5GbE LAN		
Audio	1x 3.5mm Audio Line-Out/Mic-in		
Power Input Port	3-Pin DC-In (Phoenix Type), Optional PoE, USB Type-C PD Input		

Specifications subject to change.

USA
International HQ Teguar Corporation
2920 Whitehall Park Drive
Charlotte, NC 28273
+1 704-960-1761
sales@teguar.com

EUROPE
Teguar Europe AG
Churerstrasse 54,
CH-8808 Präffikon,
Switzerland
+41 41 561 53 11
sales.EU@teguar.com

ASIA
Teguar Taiwan Ltd.
Rm. A, 28F-12., No.99, Sec. 1,
Xintai 5th Rd., Xizhi Dist.,
New Taipei City 221, Taiwan
(R.O.C.) +886 2 7751 5319
sales@teguar.com.tw

